

LDO系列 >>>

产品型号	输入(V)		最大负载 电流(A)	输出电压 范围(V)	低压差	PSRR	噪声	负载跳变	静态电 流(mA)	封装
	最小	最大								
AWL5963AAR-18	2.3	20	1.5	1.8	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOP8L
AWL5963AAR-25	2.3	20	1.5	2.5	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOP8L
AWL5963AAR-33	2.3	20	1.5	3.3	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOP8L
AWL5963AAR-ADJ	2.3	20	1.5	1.21-20	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOP8L
AWL5963KAR-18	2.3	20	1.5	1.8	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	TO263-5L
AWL5963KAR-25	2.3	20	1.5	2.5	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	TO263-5L
AWL5963KAR-33	2.3	20	1.5	3.3	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	TO263-5L
AWL5963KAR-ADJ	2.3	20	1.5	1.21-20	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	TO263-5L
AWL5963SDR-18	2.3	20	1.5	1.8	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOT223-3L
AWL5963SDR-25	2.3	20	1.5	2.5	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOT223-3L
AWL5963SDR-33	2.3	20	1.5	3.3	340mV@1.5A	60dB@120Hz	15uV _{RMS}	<1mV	1.5	SOT223-3L
AWL5764KAR-ADJ	2.7	20	3.0	1.21-20	340mV@3A	69dB@120Hz	12uV _{RMS}	<1mV	2.7	TO263-5L
AWL5764KAR-18	2.7	20	3.0	1.8	340mV@3A	69dB@120Hz	12uV _{RMS}	<1mV	2.7	TO263-5L
AWL5764KAR-25	2.7	20	3.0	2.5	340mV@3A	69dB@120Hz	12uV _{RMS}	<1mV	2.7	TO263-5L
AWL5764KAR-33	2.7	20	3.0	3.3	340mV@3A	69dB@120Hz	12uV _{RMS}	<1mV	2.7	TO263-5L
AWL5764KAR-50	2.7	20	3.0	5.0	340mV@3A	69dB@120Hz	12uV _{RMS}	<1mV	2.7	TO263-5L

